

ROTE THIS TEST Instruments

Model 8C175 ROOTS® Meter



Features

- Lightweight Aluminum Construction
- Rugged Hard Coated Cylinder, Headplates and Impellers
- Compact Size
- Multi-position Mounting
- 175 PSIG (1200kPa) Working Pressure
- Low Maintenance
- Long Service-life
- Simple Installation: I-I/2" NPT Male Connections
- Available in English and Metric

The 8C175 CTR ROOTS® Meter is the smallest, lightest and most versatile rotary gas meter ever produced. Permanent accuracy, rugged construction, wide rangeability and simple field testing add up to the best investment in gas measurement equipment your company can make.

Testing

All are units subjected to rigorous hydrostatic, leak, starting and running differential test.

Accuracy and differential data is furnished for 100% and 10% of rated capacity from positive displacement bell provers.

Capacities

ENGLISH - ATM. PRESS. = 14.4 PSIA, BASE = 14.73 PSIA, BASE TEMP. = 60°F											
PRESSURE (PSIG)	0	I	5	15	25	50	75	100	125	150	175
CAPACITY (SCFH)	800	840	1050	1600	2140	3500	4860	6210	7570	8930	10300
METRIC - ATM. PRESS. = 101.325 kPa, BASE = 101.325 kPa, BASE TEMP. = 15°C											
PRESSURE (kPa)	0	15	50	100	200	400	500	700	860	1000	1200
CAPACITY (Sm³/h)	22.6	26	34	45	67	112	134	179	215	245	290
METRIC - ATM. PRESS. = 1.01325 BAR, BASE = 1.01325 BAR BASE TEMP. = 15°C											
PRESSURE (kPa)	0	.15	.5	1	2	4	5	7	8.6	10	12.0
CAPACITY (Sm³/h)	22.6	26	34	45	67	112	135	180	215	245	290
METRIC - ATM. PRESS. = 1.0332 Kg/cm², BASE = 1.0332 Kg/cm², BASE TEMP. = 15°C											
PRESSURE (kPa)	0	.15	.5	I	2	4	5	7	8.6	10	12.0
CAPACITY (Sm³/h)	22.6	26	34	45	67	112	135	180	215	245	290

Specifications

	English	Metric
Max. Working Pressure	175 PSIG	1200 kPa
Connection Size	I-I/2" NPT, Male Thread	I-I/2" NPT, Male Thread
Weight	6 lbs	2.72 kg
Temp. Range	-40°F to +140°F	-40°C to +60°C
Oil Level Gauge	Bull's-Eye On End Covers	Bull's-Eye On End Covers
Oil Capacity (Top Inlet)	.95 oz.	28 ml
Oil Type	Versa Temp #2	Versa Temp #2
Differential Taps	I/4" NPT	I/4" NPT
Mounting	Top, Side or Bottom Inlet	Top, Side or Bottom Inlet
Impeller Type	Figure "8" Lobed	Figure "8" Lobed

Physical Dimensions

21.7 cm Length 8-9/16 inches Width 3-5/16 inches 8.4 cm 9-11/16 inches (approx.) 24.6 cm Height Construction Hard Coat Anodized Aluminum Hard Coat Anodized Aluminum Impellers, Headplates and Cylinder Impellers, Headplates and Cylinder 5 Digit with Reading \times 100 = ACF 7 Digit with Reading $x I = m^2$ Counter 0.02m³ Test Increment I ACF Test Increment



Dresser Roots Meters & Instruments

Inside US Ph: 800.521.1114 Outside US Ph: 832.590.2303

Fax: 800.335.5224 Fax: 832.590.2494 www.rootsmeters.com

Dresser, Inc.